


TF0405194
STANDARD VERSION
PA66
GREY



TF0405195
HI TEMP VERSION
PBT
RED

NOTES

WORKING TEMPERATURE
TF0405194 (PA66): -20°C to +85°C
TF0405195 (PBT): -20°C to +120°C

O-RING
MATERIAL: NITRILE RUBBER
HARDNESS: 50 SHORE
SIZE: Ø8.0 x 1.5

VENT PILL
MODIFIED ACRYLIC CO-POLYMER,
REPEL TREATED FOR SUPERIOR
HYDRO/OLEOPHOBICITY

THICKNESS: 203µm (0.008")
WATER BREAKTHRU: 505mbar (7.33psi)
MAX AIRFLOW: 50.55 (LPM/cm²/bar)

PANEL HOLE SIZE
10.6-10.8 x 5.0

ISSUE	DATE	SIG	REMARKS
1	11/05/07		SALES DRAWING

<p>THIRD ANGLE PROJECTION ALL DIMENSIONS IN MM</p>	SCALE	MATERIAL	SEE NOTES
	2:1 UNLESS SPECIFIED	COLOUR	SEE NOTES
		TOLERANCE	NOT SPECIFIED
<p>TECH-FAST.COM email: sales@tech-fast.com web: www.tech-fast.com</p>	DRAWN	CJD	
	DATE	11/05/07	

© Tech-Fast.Com Limited	
<small>THESE DRAWINGS AND THE SPECIFICATIONS, AND THE DATA CONTAINED THEREIN ARE THE PROPERTY OF TECH-FAST.COM LIMITED, ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT PRIOR WRITTEN PERMISSION OF TECH-FAST.COM LIMITED BE PRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT THE MANUFACTURE OR ARTICLES FOR TECH-FAST.COM LIMITED.</small>	
DESCRIPTION	PART No.
HYDRO/OLEOPHOBIC FILTER	TF0405194/5